

New Product Announcement

PART#: OPT1200 12V Performance Charger & Maintainer







AC Input: 100 to 120 VAC, 60 Hz 3.5 Amps

DC Output: Up to 14.9 VDC Digitally & Temperature Controlled

Charge Mode: Up to 12 Amps (Clamps), Up to 4 Amps (Aux.)

Maintain Mode: Up to 4 Amp (Clamps & Aux.) DC USB Output: 5.0 VDC, Up to 1 Amp

Battery Types: AGM and Flooded (Lead Acid) Batteries

- 12V Auto / Marine - 12V Motorcycle / Power Sports

12V OPTIMA and High Performance AGM Batteries
- Starting AGMs OPTIMA RedTop & BlueTop
- Dual Purpose AGMs OPTIMA YellowTop & BlueTop

Cables: 6' AC and DC Cable, 6' Maintainer Cable

Size: 10" x 7.5" x 6.5"

Weight: 4.8 lbs.

Features

Microprocessor-controlled Enhances the performance of OPTIMA and other AGM batteries Charges, conditions and maintains 12-volt AGM and traditional batteries Recovers deeply discharged batteries and extends battery life

LCD battery charging gauge and quick-set selections for easy operation Integrated (+) charging clamp LED work light with nonslip grips USB charging port compatible with smartphones, cameras and tablets Battery maintainer port and cable for stored vehicles High-efficiency 12-amp charging outperforms conventional chargers

PART#: OPT400 12V Performance Charger





AC Input: 100 to 120 VAC, 60 Hz, 0.75 Amps

DC Output: Up to 14.9 VDC Digitally & Temperature Controlled

Charge Mode: Up to 4 Amps (Large Batteries), Up to 3 Amps (Small Batteries)

Battery Types: AGM and Flooded (Lead Acid) Batteries

12V Auto / Marine

- 12V Motorcycle / Power Sports

12V OPTIMA and High Performance AGM Batteries
- Starting AGMs OPTIMA REDTOP & BLUETOP
- Dual Purpose AGMs OPTIMA YELLOWTOP & BLUETOP

Cables: 6' AC and DC Cables Size: 7.1" x 3.9" x 2.7"

Automatically maximizes battery life and performance with a built-in battery health mode Recovers discharged batteries other chargers cannot Hybrid LED battery charging gauge with LCD display Dual purpose hook and tilt stand design or hang it with the included wall organizer bracket Quick set battery type selection for easy operation

Interchangeable battery clamps and ring terminals Reverse polarity and over temperature protection At-a-glance battery connected and check battery icons Ambient air temperature compensation during charging Pre-charge battery status display mode Charges at a maximum rate of 4 amps